INSTALLATION INSTRUCTIONS

- STEP 1 The Kozy Kollar will work on a 0 to 12 pitch roof. After selecting the area where the Kollar is to be installed. Remove any nails that penetrate the roof in the area of the lower mounting plates. This can be done by positioning a sawzall at a right angle to the nail and cutting it off flush with the sheathing.
- STEP 2 Using the template supplied mark the area to be cut out. Use the centerline mark on the template to locate where your pipe is to penetrate the roof. Care should be taken when positioning the template. To set the roof Kollar square with the outside of the building the template should be aligned with a framing member (roof rafter, plywood seam, ect.). The outside of the template should be kept 2" from rafters or other obstructions.
- STEP 3 Using a sawzall fitted with a rough-in blade cut out the marked rectangle from the roof. It is critical to cut along the line as close as possible. Do not cut outside the line. The downward pull of the blade will cut the shingles cleanly. <u>The Kozy Kollar can be installed in any weather just clear the roof of any debris, ice, or snow where the Kollar will sit.</u>
- STEP 4 Install the four corner studs in to the Kozy Kollar, apply a thin bead of the gasket sealant supplied with the Kozy Kollar into the caulking channel of the primary seal. Pass the Kollar through the hole cut in the roof. Set the Kozy Kollar on the roof the four corner studs will hold the Kollar in place.
- STEP 5Install the remaining studs, the lower mounting
plates, and rod couplings. The Kozy Kollar
REQUIRES COMPRESSION TO WORK.
Starting with the top studs tighten the rod
couplings to approximately 3 foot pounds.

If a Torque Wrench is not available tighten the rod couplings until the lower mounting plates begin to distort.



For Architectural and Conventional Shingles Will work on metal, rolled roofing and EPDM roofs visit our website for details Proudly Made In America

Installation Video Can Be Seen At <u>www.kozykollar.com</u>

Kozy Kollar Mfg. Pelham NH 603-598-1192 Fax 603-598-1192

Limited Ten Year Warranty

Kozy Kollar Inc. warrants that the products sold shall be of the standard quality of seller and buyer assumes all risk and liability resulting from the use of the goods, whether used singly or in combination with other goods. the goods sold shall be free of defects in workmanship or material. Products when properly installed shall be free from defects and form a weather tight seal. should any failure to confirm to this warranty appear within ten years from date of purchase. Kozy Kollar Inc. shall replace the product after return of the defective product. This limited warranty does not cover product failure caused by improper installation, application over deteriorated or improperly installed roof shingles or exposure to chemicals or environmental pollutants SELLER MAKES NO OTHER WARRANTY, EXPRESS OR IMPLIED, AND MAKES NOT WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR ANY PARTICULAR PURPOSE. THERE SHALL BE NO LIABILITY FOR SPECIAL INDIRECT, CONSEQUENTIAL, OR INCIDENTAL DAMAGES.

